


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		DESIGNED PER HELI PRODUCTS TOOLS.	9/11/2009	WP	DW
2		ADDED ONE MORE -03 PIN, FLAG AND CABLE TIE.	6/14/2010	WP	DW
3		MOVED LENGTH B DIMENSION TO Ø.118in. HOLE CENTERLINE & ADDED 1.5mm TO -01 THRU -09 PINS IN TABLE. ADDED A TOLERANCE TO Ø.118in HOLE TO ACHIEVE A LIGHT PRESS FIT FOR -11. CH'D HOLE FROM Ø.118 TO Ø.113 FOR CABLE TIES. END OF PIN PER S.E.	12/15/2010	RJC	RW
4		CORRECTED PIN VIEW SHEET 1 AND CH'D Ø.113 [Ø2.9mm] HOLE TO Ø.118 [Ø3.0mm] PER G.E.	5/9/2012	RJC	GE
4A		CH'D T/N WAS RBEA94-2706-00 IS RBE350A94-2706-00.	11/6/2013	RJC	RW
5	15-0120	UPDATED TO NEW DRAFTING STANDARDS. CH'D TOLERANCE BLOCK WAS .XXX ± .004 IS .XXX ± .005. ADDED P/N'S -01A, -03A, -05A, -07A, -09A. CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS.	5/26/2015	DPD	JAG
6	16-0281	UPDATED TO DRAFTING STANDARD. -01, -03, -05, -07, -09 ADDED FINISH SPEC QSMI-6.2.2. B.O. REV D. ADDED -17, -19. NOTE: -01A, -03A, -05A, -07A, -09A CH'D DIM WAS 2X Ø.118 +.001/-000 THRU ALL IS Ø.1180/.1176 THRU ALL (P.F. -11). ADDED DIM Ø.12 THRU ALL. ADDED ENGRAVE DASH No., ADDED ENGRAVE DASH No. COLUMN TO TABLE.	1/12/2017	RJC	JAG





ASSY QTY	ASSY QTY	ASSY QTY	ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
				X		-01	4	PIN			2
				1		-01A		PIN SHAFT	O-1	Ø6mm X 3 FT (MCMaster-CARR #88625K65) MODIFIED	3
			X			-03	2	PIN			2
			1			-03A		PIN SHAFT	O-1	Ø8mm X 3 FT (MCMaster-CARR #88625K67) MODIFIED	3
		X				-05	1	PIN			2
		1				-05A		PIN SHAFT	O-1	Ø8mm X 3 FT (MCMaster-CARR #88625K67) MODIFIED	3
	X					-07	1	PIN			2
	1					-07A		PIN SHAFT	O-1	Ø6mm X 3 FT (MCMaster-CARR #88625K65) MODIFIED	3
X						-09	1	PIN			2
1						-09A		PIN SHAFT	O-1	Ø8mm X 3 FT (MCMaster-CARR #88625K67) MODIFIED	3
1	1	1	1	1	B/O	-11		DOWEL PIN	STEEL	Ø3mm X 40mm (MCMaster-CARR #91595A142)	2
					B/O	-13	1	RE-SEALABLE PLASTIC BAG		5 IN X 6 IN APPROX.	N/S
A/R	A/R	A/R	A/R	A/R	B/O	-15		LOCITITE 680			2
1	1	1	1	1	B/O	-17		FLAGS, REMOVE BEFORE FLIGHT	NYLON	NAS 1756-12	2
1	1	1	1	1	B/O	-19		CABLE TIE	BLACK NYLON	(MCMaster-CARR #7189K31)	2
ASSY -09	ASSY -07	ASSY -05	ASSY -03	ASSY -01							

		TITLE	
		RIGGING PIN SET	
DWG NO.		RBE350A94-2706-00	
		REV 6	
MATERIAL		UNLESS OTHERWISE SPECIFIED	
TREAT		DIMENSIONS ARE IN INCHES	
FINISH		.XXX ± .005 FRACTIONS ± 1/8	
		.XX ± .01 ANGLES ± 5°	
		.X ± .1 SURFACES = 125°	
SPEC		1. BREAK ALL SHARP EDGES	
		.015 x 45° OR .015R	
DRAWN BY:		PERRITT	
CHECKED:		DUERFELDT	
OPPS APPR:		ANDERSON	
QA APPR:		LINDSAY	
APPROVED:		GILBERT	
SCALE		1:3	
DATE		9/11/2009	
		SHEET 1 OF 3	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
6	16-0281	-01, -03, -05, -07, -09 ADDED FINISH SPEC QSMI-6.2.2, B.O. REV D. ADDED -17, -19, NOTE Δ.	1/12/2017	RJC	JAG



ASSY P/N	A P/N
-01	-01A
-03	-03A
-05	-05A
-07	-07A
-09	-09A

NOTE:

1 USE LOCTITE 680 TO ASSEMBLE.




-01, -03, -05, -07, -09

PIN

DART AEROSPACE	
TITLE RIGGING PIN SET	
DWG NO. RBE350A94-2706-00-01	REV 6
MAT'L REPT TREAT FINISH SPEC	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 1° .X ± .1 SURFACES = 125°
DRAWN BY: PERRITT	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	EUROCOPTER AS350/355
SCALE 1:3	DATE 9/11/2009
SHEET 2 OF 3	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3		MOVED LENGTH B DIMENSION TO Ø.118in. HOLE CENTERLINE & ADDED 1.5mm TO -.01 THRU -.09 PINS IN TABLE. ADDED A TOLERANCE TO Ø.118in HOLE TO ACHIEVE A LIGHT PRESS FIT FOR -.11. CH'D HOLE FROM Ø.118 TO Ø.113 FOR CABLE TIES. END OF PIN PER S.E.	5/26/2015	RJC	RW
4	15-0120	CH'D TOLERANCE BLOCK WAS .XXX ± .004 IS .XXX ± .005.	5/26/2015	DPD	JAG
6	16-0281	-01A, -03A, -05A, -07A, -09A CH'D DIM WAS 2X Ø.118 +.001/-.000 THRU ALL IS Ø.1180/.1176 THRU ALL (P.F. -11). ADDED DIM Ø.12 THRU ALL. ADDED ENGRAVE DASH No., ADDED ENGRAVE DASH No. COLUMN TO TABLE.	1/12/2017	RJC	JAG



-01A, -03A, -05A, -07A, -09A

PIN SHAFT

ENGRAVE	PIN DIMENSION TABLE		
DASH No.	P/N	ØA	LENGTH B
-01	-01A	6mm	2.028
-03	-03A	8mm	5.177
-05	-05A	8mm	3.012
-07	-07A	6mm	4.783
-09	-09A	8mm	1.240

DART AEROSPACE	
TITLE RIGGING PIN SET	
DWG NO. RBE350A94-2706-00-01A	REV 6
MAT'L O-1	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -01, -03, -05, -07, -09	.XXX ± .005 FRACTIONS ± 1/8
SPEC	.XX ± .01 ANGLES ± 5°
	.X ± .1 SURFACES = 125
DRAWN BY: PERRITT	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	EUROCOPTER AS350/355
SCALE 1:1	DATE 9/11/2009
	SHEET 3 OF 3